## **Valor** PORTRAIT SERIES PRESIDENT FREESTANDING STOVE

530ILN Portrait Engine with 531CSB President Freestanding Stove (shown with Log Set and Red Brick)

Efficient. Versatile. Distinct.

Radiant Gas Fireplaces

Crafted with detail and inspired by classic design, the President Freestanding Stove is perfect for upgrading traditional spaces. Projecting a mere 13" inches into the room, the President leaves plenty of space for additional home styling and décor. Capable of both top and rear vent applications, the President shows great freestanding as well as tight against an exterior wall. Solid cast iron encases a proven Valor Portrait engine, assured to provide warmth and comfort for many years to come.

# **OF PRESIDENT FREESTANDING STOVE**

### **PRESIDENT FREESTANDING STOVE - FIREPLACE COMPONENTS**

#### 530ILN Portrait Log Effect Engine Direct Vent NG 530ILP Portrait Log Effect Engine Direct Vent LPG ENGINES 530ICN Portrait Coal Effect Engine Direct Vent NG 530ICP Portrait Coal Effect Engine Direct Vent LPG 530IRN Portrait Rock Effect Engine Direct Vent NG **530IRP** Portrait Rock Effect Engine Direct Vent LPG 531CSB President Freestanding Stove (2 castings - 531-1CSB and 531-2CSB) 551DVK Direct Vent Kit - Valor sidewall vent terminal 556CLA Co-linear Adapter - converts co-axial vent to 2-3" vent liners (insert application) 559CLT Co-linear Terminal - chimney liner termination cap (for use with 556CLA) ACCESSORIES 559SFK Square Flashing Kit for 559CLT (for masonry applications) 817VAK Vent Adapter - black, Simpson Dura-Vent 835TG Outdoor Terminal Guard 555CFK Circulating Fan Kit - variable speed, thermally activated 554LPK Conversion Kit - NG to LPG 567FGP Firebox Grille Panel - roof panel (530ILN/P or 530IRN/P only) 1265WSK Valor Wall Switch Kit - light/turn off pilot & adjust flame size WARRA

Custom build your own fireplace - design.valorfireplaces.com

Fuel Bed

Options

Log


Coal

Rock

Log

Coal

## **PR**( DIM



Rock \*\* EnerGuide Ratings and Outputs have been determined without a fan/blower, using the CSA P.4.1-02 test method

\*\* A.F.U.E. (Annual Fuel Use Efficiency) tested as per 10CFR - 430.23

Certified to ANSI Z21.88 / CSA 2.33 Vented Gas Fireplace Heater Standard

Min.

Input

6,500

12,500


BTU/hr

CAN 1-2. 17 Gas Fired Appliances For Use at High Altitude

#### ABOUT OUR EFFICIENCY RATINGS

At Valor we use recognized Canadian and US government test methods for determining energy efficiency performance. This ensures our products will perform in your home as rated. Beware of misleading "steady state" efficiency claims made by manufacturers using their own "in-house" test methods. For more information please visit our website at valorfireplaces.com

All product information is accurate at time of printing and is subject to change. Note: Printed images may vary from actual product.



**MODEL/FUEL** 

Fuel

NG

LPG

Max.

Input BTU/hr

20,500

19,000

Model

530ILN

530ICN

530IRN

530ILP

530ICP

530IRP



### Valor THE WISE WAY TO HEAT



Copyright Miles Industries Ltd. 2010 Proudly Made in North America BR53110F

Printed on recycled paper

OR ITT PROGRAM	FIREBED OPTION
OMFO <sup>®</sup>	1
ODUCT ENSIONS	b.
-13"	2.
	3.

**INTERIOR LINER** (REVERSIBLE)

24-1/2

- 1. Traditional Log Set
- 2. Contemporary Rock Effect
- 3. Black Coal Set

